

HYBRID INVERTER

THREE PHASE:
HP3-5K/6K/8K/10K/12K D2, HP3-15K/20K/25K/30K T2
HP3-5K/6K/8K/10K/12K/15K L2
HP3-15K/20K/25K/30K/36K M2

As the core of the energy storage solution, LIVOLTEK three phase hybrid inverter offers flexible and social-able solutions for both residential and commercial applications. With the ability of scalable battery storage, the high-voltage inverter facilitate powerful energy backup and also present high self-consumption with optimized built-in EMS to reduce energy cost.

High Performance

- 200% DC input oversizing
- 200% overload for backup loads
- Seamless switch for backup mode

Flexible Application

- Supports parallel function
- 100% unbalanced output
- Compatible with generator

Smart Management

- Peak shaving mode
- Support half-wave loads
- Remote control and upgrade

 Safe and Reliable

- AC & DC SPD type II
- AFCI function optional
- Touch-free, one-click communication



HYBRID INVERTER

HP3-5K/6K/8K/10K/12K D2, HP3-15K/20K/25K/30K T2

INVERTER

Model	HP3-5KD2	HP3-6KD2	HP3-8KD2	HP3-10KD2	HP3-12KD2	HP3-15KT2	HP3-20KT2	HP3-25KT2	HP3-30KT2
PV Input									
Max. PV Input Power	10000Wp	12000Wp	16000Wp	20000Wp	24000Wp	30000Wp	40000Wp	50000Wp	60000Wp
Max. PV Input Voltage	1000V								
Nominal Input Voltage	600V								
MPPT Voltage Range	150 V ~ 950 V								
No. of MPPTs/Strings per MPPT	2 / (1+1)			2 / (2+1)		3 / (2+2+1)		3 / (2+2+2)	
Max. PV Current	16A / 16A			32A / 16A		32A / 32A / 16A		32A / 32A / 32A	
Max. Short Circuit Current	20 / 20A			40A / 20A		40A / 40A / 20A		40A / 40A / 40A	
AC Output @ Grid									
Max. AC Input Power	10000Wp	12000Wp	16000Wp	20000Wp	20000Wp	30000Wp	40000Wp	40000Wp	40000Wp
Mac. AC Input Current	15.5A	18.6A	24.8A	31.0A	31.0A	43.5A	58.0A	58.0A	58.0A
Nominal AC Output Power	5000W	6000W	8000W	10000Wp	12000Wp	15000Wp	20000Wp	25000Wp	30000Wp
Nominal AC Voltage	3W + N + PE, 380V, 400V, 415V								
AC Frequency	45 ~ 55Hz / 55 ~ 65Hz								
Max. AC Current	7.6A	9.1A	12.1A	15.2A	18.2A	22.8A	30.4A	37.9A	45.5A
THDi @Rated Power[%]	< 3%								
Power Factor	~1 (Adjustable from 0.8 Leading to 0.8 Lagging)								
EPS Output @ Off Grid									
Nominal EPS Power	5000W	6000W	8000W	10000Wp	12000Wp	15000Wp	20000Wp	25000Wp	30000Wp
EPS Peak Power (10s)	12kW		18.6kW			35kW		39.3kW	
Nominal Output Voltage	3W + N + PE, 220 / 380V, 230 / 400V, 240 / 415V								
Nominal Frequency	50Hz / 60Hz								
Nominal Output Current	7.3A	8.7A	11.6A	14.5A	17.4A	21.8A	29.0A	36.3A	43.5A
THDv @Linear Power[%]	< 3%								
Battery Input									
Battery Type	Lithium								
Battery Voltage	100V ~ 700 V								
Max. Charge/Discharge Current	50A / 50A								
Communication with BMS	CAN								
Efficiency									
Max. Efficiency	97.90%	97.90%	98.00%	98.00%	98.00%	98.10%	98.10%	98.20%	98.20%
Euro Efficiency	97.20%	97.30%	97.40%	97.50%	97.50%	97.70%	97.70%	97.80%	97.80%
General Data									
Dimension (W*H*D)	540*470*210 mm					595*485*235 mm			
Weight	26kg					38kg			
Cooling	Natural Convection					Intelligent Fan			
Protection Rating	IP65								
Mounting Method	Wall-mounted								
Operating Temperature Range	-25 °C to +60 °C								
Display	LED & APP								
Communication	Wi-Fi / DO / DI / RS485								
Protection Function	Islanding Protection, PV DC Reverse Polarity Protection, DC Short Circuit Protection Device, AC Short Circuit Protection Device, PV DC Overcurrent Protection, AC Overcurrent Protection, Leakage Current Protection, Over/Under Frequency Protection, Over/Under Voltage Protection, Insulation Resistance Protection, Over-Temperature Protection, AC Current Imbalance Protection, Arc Detection Protection, Buzzer Warning								